



UVZone Shoe Sanitizing Station (SSS) Technical Specifications

PATHO₃GEN SOLUTIONS SSS™

OVERALL DIMENSIONS	24" x 24" x 2"H (61 X 61 X 5 CM) WEIGHT: 33 LBS (15 KG)
LAMP TYPE; UV	QTY (4); 15.2" (386MM) UV LAMPS
LAMP TYPE; OZONE	QTY (2); 14" (357MM) OZONE LAMPS
BALLAST	QTY (3); DIMMABLE
LAMP LIFE	10,000 HOURS ACCUMULATED ON TIME TO 80 % OUTPUT
AC POWER INPUT	125V~, 60 HZ; 1 AMP
POWER CABLE	18/3 SJT POWER CORD
FINISH	POWDER COAT PAINT

ELECTRICAL SPECIFICATIONS

AC INPUT	120VAC; 60 HZ, 1.0 AMP MAX.
MODE OF OPERATION	CONTINUOUS
CONTROLS	ON/OFF FROM EXTERNAL POWER
STANDARDS	UL 61010-1:2012, REVISED JULY 15, 2015

ENVIRONMENTAL REQUIREMENTS AND OPERATING

ENVIRONMENTAL OPERATING TEMPERATURES	50°F to 104°F / 10°C to 40°C
ATMOSPHERIC PRESSURE	500hPa - 1060hPa/ 375 to 795 mmHg
HUMIDITY	10% - 95% RH, NON-CONDENSING

TYPE OF PROTECTION AGAINST ELECTRICAL SHOCK	CLASS I
DEGREE OF PROTECTION AGAINST ELECTRICAL SHOCK	B
DEGREE OF PROTECTION AGAINST INGRESS OF WATER (IEC 529)	IPX1

STORAGE SPECIFICATIONS

STORAGE AND TRANSPORT ENVIRONMENTAL INFO	ACCEPTABLE TEMPERATURE RANGE	-15°C TO 40°C (5° F TO 104° F)
	RELATIVE HUMIDITY	10 TO 93 %RH
	AIR PRESSURE	500 TO 1060 HPA(15 TO 31 INHG)
OPERATING ENVIRONMENTAL INFO	ACCEPTABLE TEMPERATURE RANGE	10°C TO 40°C (50° F TO 104° F)
	RELATIVE HUMIDITY	30 TO 75 %RH
	AIR PRESSURE	700 TO 1060 HPA (21 TO 31 INHG)
	MAXIMUM ALTITUDE	3000 METERS